

## Claims

- [c1] A cooking grate comprising:  
a frame comprising an exterior frame element;  
at least one interior frame element comprising a cooking utensil supporting surface, said cooking utensil supporting surface elevated from said exterior frame element; and  
at least one recessed surface extending from said cooking utensil supporting surface, a top of said recessed surface separated from a top of said cooking utensil supporting surface, thereby providing a gap for passage of a burner flame.
- [c2] A cooking grate in accordance with Claim 1, said grate comprising a first interior element and a second interior element, each of said first interior element and said second interior element comprising a recessed surface.
- [c3] A cooking grate in accordance with Claim 1 further comprising a plurality of support fingers extending from said interior frame element and said exterior frame element.
- [c4] A cooking grate in accordance with Claim 3 wherein said support fingers comprise elliptical arcs.
- [c5] A cooking grate in accordance with Claim 1 wherein said cooking grate is substantially rectangular.
- [c6] A grate assembly for a gas cooking appliance, said grate assembly comprising:  
at least one exterior frame element;  
at least one support finger extending from said frame, said support finger comprising a top surface extending above said at least one exterior frame element;  
at least one interior frame element comprising a top surface extending above said at least one exterior frame element, said top surface of said interior frame element substantially coplanar with said top surface of said support finger; and  
at least one recessed surface extending from said top surface of said interior frame element, said recessed surface defining a clearance for passage of a



first recessed portion and said second recessed portion located on opposite sides of said cross member.

- [c14] A grate assembly in accordance with Claim 11 further comprising at least one support finger extending from said frame, said support finger extending in an elliptical arc.
- [c15] A grate assembly in accordance with Claim 11 further comprising a bridge spacer section comprising a top surface coplanar with said top surface of said interior frame element, and at least one recessed portion extending from said top surface of said bridge spacer section.
- [c16] A grate assembly in accordance with Claim 15 wherein said recessed surface is concave.
- [c17] A gas fired cooktop comprising:  
at least a first gas burner and a second gas burner, and;  
a grate assembly surrounding said first gas burner and said second gas burner, said grate assembly comprising an interior frame element extending between said first gas burner and said second gas burner, said interior frame element comprising a cooking utensil surface and a flame clearance recessed portion extending from cooking utensil surface.
- [c18] A cooktop in accordance with Claim 17 wherein said grate assembly comprises a rectangular grate section surrounding said first burner and said second burner.
- [c19] A cooktop in accordance with Claim 18 wherein said cooktop comprises four burners, said grate assembly comprising a first grate section, a second grate section, and a bridge spacer section therebetween.
- [c20] A cooktop in accordance with Claim 18 wherein said grate section comprises an interior cross member frame element, said recessed portion substantially centered in said cross member frame element.
- [c21] A cooktop in accordance with Claim 20 wherein said recess portion is concave.

- [c22] A gas fired cooktop comprising:  
a first gas burner and an adjacent second gas burner;  
a first grate section surrounding said first and second gas burners;  
a third gas burner and an adjacent fourth gas burner, said third and fourth gas burners adjacent said first and second gas burners;  
a second grate section surrounding said third and fourth gas burners; and  
a bridge spacer grate section extending between said first grate section and said second grate section; a top surface of each of said first grate section, second grate section, and bridge spacer section comprising a substantially coplanar utensil supporting surface; and  
a recessed surface portion extending from said utensil supporting surface between each adjacent gas burner.
- [c23] A cooktop in accordance with Claim 22 wherein said recessed surface portion is substantially centered between each adjacent burner in said first and second grate section.
- [c24] A cooktop in accordance with Claim 23 wherein at least one of said first and second grate sections is substantially rectangular.
- [c25] A cooktop in accordance with Claim 22 further comprising a plurality of elliptically extending support fingers extending from each of said first grate, second grate and said bridge spacer section.
- [c26] A cooktop in accordance with Claim 22 wherein said recessed portion is concave.